

TUTELA TRANSMISSION GI/A Cod. 1500

DESCRIPTION

Oil for automatic gearshift and power steering of cars, and light commercial vehicles, industrial vehicles and for all hydraulic drives.

CHARACTERISTICS

- Optimal fluency when cold in order to reduce power absorption and improve transmission performance.
- Optimal anti-foaming properties in order to guarantee the maximum lubrication performance and optimum heat exchange.
- Excellent anti-oxidant characteristics for improved lubricant endurance.
- High viscosity index in order to optimise the response of the servo-controls in every operating temperature condition.
- Excellent anti-wear properties to improve the durability of the mechanical components.

TUTELA GI/A exceeds the strict quality requirements of the major European Manufacturers and can be used in machinery of every make, type and power rating.

ADVICE ON USE

TUTELA GI/A is available in SAE 10W grade for use it in every season of the year.

Replacement for tractors and agricultural machinery should be as indicated by the Manufacturer, however, not beyond 800 hours of work.

Replacement for industrial vehicles should be as indicated by the Manufacturer, however, at least once a year.

On cars, changes should be made every 40,000 km.

For motorcycles replacement should be as indicated by the Constructor.

RECOMMENDED BY

Fiat, Lancia, Alfa Romeo, Maserati, Iveco, Astra, Fiat Tractors, Laverda, Agrifull.

TECHNICAL DATA

ATF DEXRON II D,
IVECO 18-1807 CLASSE AG2, CONTRACTUAL TECHNICAL REF. N°I002.B92,
FIAT 9.55550-AG1 CONTRACTUAL TECHNICAL REF. N°F002.B92,
VOITH 55.6335.32 Performance, ZF TE-ML 04D,
ZF TE-ML 14A, MB 236.1 Performance,
MB 236.5 Performance,
MAN 339 TYPE Z1 and V1 Performance,
MAN 339 TYPE Z2 and V2 Performance,
CAT TO-2 Performance

