

TECHNICAL CHARACTERISTICS

URANIA DAILY LS

PRODUCT CODE: 1358

APPLICATION

Fully synthetic lubricant specifically formulated for IVECO Daily engines and in particular for latest generation engines (EURO V). Its "Low Saps" formula allows excellent protection of the particulate filter (DPF) and has high level Fuel Economy properties.

SPECIFICATIONS

SAE 5W-30, IVECO 18-1811 CLASSE SC1, CONTRACTUAL TECHNICAL REF. N°I510.D09

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
DENSITY @ 15°C	ASTM D 5931	g/cm3	0,850
VISCOSITY @ 100°C	ASTM D445	cSt	10,1
VISCOSITY INDEX	ASTM D 2270	--	> 150
POUR POINT	ASTM D 97	°C	< -36
FOAM @ 24°C	ASTM D 892	cc/s	TRACES/0
T.B.N.	ASTM D 2896	mg KOH/g	> 7
ACIDITY NUMBER	ASTM D 974	mg KOH/g	1.7

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

03/2014